# Convenient. Assuring. Durable.

AMSCO Flexmatic Scrub Sink

## All STERIS scrub sinks are convenient and easy to use

- Hands-free water control - knee activated panel turns water on and off
- Hands-free soap – 2 cc. of soap are released with each push of the foot pump or knee operated dispenser
- Two different faucet options:
  - Standard "rose" spray head produces a shower head type pattern without aerating the water
  - Optional laminar flow head delivers a consistent stream of non-aerated water

## Reassuring Safety

- Integrated eye-wash station - this faucet attachment provides convenient OR access with an emergency eye wash station
  - When water is turned on with knee panel, one pull of the center knob releases both orange safety caps to provide instant eye flushing*
  - When knob is not activated, faucet functions as a scrub sink
- Optimum water temperature – the built-in thermostatically controlled mixing valve provides water temperatures of up to 115° F (46° C)

Digital timer

Optional laminar flow head with optional eye wash

Optional infrared sensor Amsco Flexmatic Scrub Sink Only

Optional divider screen AMSCO Flexmatic Scrub Sink Only

STERIS

# High Quality Surgical Scrub Sinks

## AMSCO® Flexmatic® Scrub Sink

## Streamline® Scrub Sink

### Built for Your OR

- Easy cleaning – Continuous welded compartments and coved compartments constructed entirely of stainless steel
- Timed scrubbing - optional digital timer ensures adequate scrubbing time
- Optional infrared sensor turns water on and off
- Upgradeable knee-operated internal soap dispenser
- **Available models:** 1, 2 or 3 station

### Stands up to Repeated Washings

- Durable scrub sinks thermoformed of high-quality KYDEX®** polymeric material
- Seamless large coved basin is easy to clean and reduces potential contaminants
- **Available models:** 1 or 2 station
- Optional foot pump soap dispenser

| Models | AMSCO Flexmatic Scrub Sink | | | Streamline Scrub Sinks | |
|---|---|---|---|---|---|
| | 1-station | 2-station | 3-station | 1-station | 2-station |
| Dimensions (W x D x H) | 32 x 27 9/32 x 51 1/2" (813 x 692 x 1308 mm) | 64 x 27 9/32 x 51 1/2" (1626 x 692 x 1308 mm) | 96 x 27 9/32 x 51 ½" (2438 x 692 x 1308 mm) | 32 x 27 9/32 x 51 ½" (813 x 692 x 1308 mm) | 64 x 27 9/32 x 51 ½" (1626 x 692 x 1308 mm) |
| Laminar flow faucet head | optional | optional; both faucets would have same style head | optional; all faucets would have same style head | optional | optional; both faucets would have same style head |
| Eye wash station attachment | optional | optional; can be attached to either left or right faucet | optional; can be attached to any of the three faucets | optional | optional; can be attached to either left or right faucet |
| Infrared water control | optional | optional | optional | N/A | N/A |
| Foot pump soap dispenser | optional | optional; recommend one for each station | optional; recommend one for each station | optional | optional; recommend one for each station |
| Knee-operated internal soap dispenser | optional | optional | optional | N/A | N/A |
| Digital timer | optional | optional | optional | N/A | N/A |
| Divider Screen | N/A | optional | optional | N/A | N/A |
| Temperature safety | > 115°F (46°C) | > 115°F (46°C) | > 115°F (46°C) | > 115°F (46°C) | > 115°F (46°C) |

*Faucet-mounted eye wash stations (regardless of manufacturer) require two motions to operate them (turn water on, pull knob) and thus do not meet the provisions of ANSI Z358.1-2004; these are intended as supplemental installations to other dedicated eye washing stations.

** KYDEX is a registered trademark of Kydex LLC.

Document #M4043EN.2015-08, Rev. A
©2015 STERIS Corporation. All rights reserved.

STERIS

STERIS Corporation
5960 Heisley Road
Mentor, OH 44060-1834 ▪ USA
440-354-2600 ▪ 800-548-4873
www.steris.com